

## Cobra® MX Compatibility

All Cobramatic® and Cobramatic compatible guns are available in lengths of 15 ft, 25 ft, 35 ft, and 50 ft. Lincoln Compatible guns used with Lincoln Power Feed 25M (model K2536-4) require a kit for adaptability. Call factory for details.



**LINCOLN, 7 PIN COMPATIBILITY**  
CLASSIC CUP, 1/4" TIP

AIR COOLED	
LENGTH	MODEL NUMBER
15 ft (4.6 m)	276-815
25 ft (7.6 m)	276-825
35 ft (10.7 m)	276-835
50 ft (15.2 m)	276-850
WATER COOLED	
15 ft (4.6 m)	278-815
25 ft (7.6 m)	278-825
35 ft (10.7 m)	278-835
50 ft (15.2 m)	278-850

**MILLER, 14 PIN COMPATIBILITY**  
CLASSIC CUP, 1/4" TIP

AIR COOLED	
LENGTH	MODEL NUMBER
15 ft (4.6 m)	280-815
25 ft (7.6 m)	280-825
35 ft (10.7 m)	280-835
50 ft (15.2 m)	280-850
WATER COOLED	
15 ft (4.6 m)	282-815
25 ft (7.6 m)	282-825
35 ft (10.7 m)	282-835
50 ft (15.2 m)	282-850

**FRONIUS, 9 PIN COMPATIBILITY**  
CLASSIC CUP, 1/4" TIP

AIR COOLED	
LENGTH	MODEL NUMBER
15 ft (4.6 m)	284-815
25 ft (7.6 m)	284-825
35 ft (10.7 m)	284-835
50 ft (15.2 m)	284-850
WATER COOLED	
15 ft (4.6 m)	286-815
25 ft (7.6 m)	286-825
35 ft (10.7 m)	286-835
50 ft (15.2 m)	286-850

**EURO, 7 PIN COMPATIBILITY**  
CLASSIC CUP, 1/4" TIP

AIR COOLED	
LENGTH	MODEL NUMBER
15 ft (4.6 m)	298-815
25 ft (7.6 m)	298-825
35 ft (10.7 m)	298-835
50 ft (15.2 m)	298-850
WATER COOLED	
15 ft (4.6 m)	299-815
25 ft (7.6 m)	299-825
35 ft (10.7 m)	299-835
50 ft (15.2 m)	299-850

**MAX CUP, 3/8" TIP**

AIR COOLED	
LENGTH	MODEL NUMBER
15 ft (4.6 m)	277-815
25 ft (7.6 m)	277-825
35 ft (10.7 m)	277-835
50 ft (15.2 m)	277-850
WATER COOLED	
15 ft (4.6 m)	279-815
25 ft (7.6 m)	279-825
35 ft (10.7 m)	279-835
50 ft (15.2 m)	279-850

**MAX CUP, 3/8" TIP**

AIR COOLED	
LENGTH	MODEL NUMBER
15 ft (4.6 m)	281-815
25 ft (7.6 m)	281-825
35 ft (10.7 m)	281-835
50 ft (15.2 m)	281-850
WATER COOLED	
15 ft (4.6 m)	283-815
25 ft (7.6 m)	283-825
35 ft (10.7 m)	283-835
50 ft (15.2 m)	283-850

**MAX CUP, 3/8" TIP**

AIR COOLED	
LENGTH	MODEL NUMBER
15 ft (4.6 m)	285-815
25 ft (7.6 m)	285-825
35 ft (10.7 m)	285-835
50 ft (15.2 m)	285-850
WATER COOLED	
15 ft (4.6 m)	287-815
25 ft (7.6 m)	287-825
35 ft (10.7 m)	287-835
50 ft (15.2 m)	287-850

**MAX CUP, 3/8" TIP**

AIR COOLED	
LENGTH	MODEL NUMBER
15 ft (4.6 m)	300-815
25 ft (7.6 m)	300-825
35 ft (10.7 m)	300-835
50 ft (15.2 m)	300-850
WATER COOLED	
15 ft (4.6 m)	301-815
25 ft (7.6 m)	301-825
35 ft (10.7 m)	301-835
50 ft (15.2 m)	301-850

SEE PYTHON LX COMPATIBILITY SECTION FOR COMPLETE GUN LEAD ASSEMBLY COMPONENTS

**OPTIONAL LEAD ASSEMBLY COMPONENTS**

LENGTH	ULTRA FLEX POWER CABLE*
15 ft (4.6 m)	843-0715-15
25 ft (7.6 m)	843-0715-25
35 ft (10.7 m)	843-0715-35
50 ft (15.2 m)	843-0715-50

**ALUMINUM WELDING ONLY (COMPATIBLE GUNS)**

LENGTH	CONDUIT ASSEMBLY
15 ft (4.6 m)	615-0620-15
25 ft (7.6 m)	615-0620-25
35 ft (10.7 m)	615-0620-35
50 ft (15.2 m)	615-0620-50

**HARD WIRE WELDING\* ONLY**

LENGTH	FLAT SPIRAL STEEL CONDUIT ASSEMBLY
15 ft (4.6 m)	615-0621-15
25 ft (7.6 m)	615-0621-25
35 ft (10.7 m)	615-0621-35
50 ft (15.2 m)	615-0621-50

\*Air Cooled models only

\*Steel, stainless steel and flux core steel wires  
See accessories and consumables for liners and contact tips (pgs 21-24)