

## Python® Compatibility

All Cobramatic® and Cobramatic compatible guns are available in lengths of 15 ft, 25 ft, 35 ft, and 50 ft. Lincoln Compatible guns used with Lincoln Power Feed 25M (model K2536-4) require a kit for adaptability. Call factory for details.



### LINCOLN, 7 PIN COMPATIBILITY

AIR COOLED	
LENGTH	MODEL NUMBER
15 ft (4.6 m)	232-815
25 ft (7.6 m)	232-825
35 ft (10.7 m)	232-835
50 ft (15.2 m)	232-850
WATER COOLED	
15 ft (4.6 m)	293-815
25 ft (7.6 m)	293-825
35 ft (10.7 m)	293-835
50 ft (15.2 m)	293-850

### MILLER, 14 PIN COMPATIBILITY

AIR COOLED	
LENGTH	MODEL NUMBER
15 ft (4.6 m)	291-815
25 ft (7.6 m)	291-825
35 ft (10.7 m)	291-835
50 ft (15.2 m)	291-850
WATER COOLED	
15 ft (4.6 m)	292-815
25 ft (7.6 m)	292-825
35 ft (10.7 m)	292-835
50 ft (15.2 m)	292-850

### FRONIUS, 9 PIN COMPATIBILITY

AIR COOLED	
LENGTH	MODEL NUMBER
15 ft (4.6 m)	289-815
25 ft (7.6 m)	289-825
35 ft (10.7 m)	289-835
50 ft (15.2 m)	289-850
WATER COOLED	
15 ft (4.6 m)	290-815
25 ft (7.6 m)	290-825
35 ft (10.7 m)	290-835
50 ft (15.2 m)	290-850

### EURO, 7 PIN COMPATIBILITY

AIR COOLED	
LENGTH	MODEL NUMBER
15 ft (4.6 m)	296-815
25 ft (7.6 m)	296-825
35 ft (10.7 m)	296-835
50 ft (15.2 m)	296-850
WATER COOLED	
15 ft (4.6 m)	297-815
25 ft (7.6 m)	297-825
35 ft (10.7 m)	297-835
50 ft (15.2 m)	297-850

MK Products compatible guns have interchangeable fittings, so you can match as needed for your cooler. Both fittings require a hose retainer. Call factory for pricing.



**431-1898**  
5/16" Hose Retainer



**431-1910**  
Quick Connect Fitting



**431-1893\*** Nipple  
**753-3379\*** Left-Hand Threaded Fitting  
*\*Must be ordered together*

### GUN LEAD ASSEMBLY COMPONENTS - PYTHON COMPATIBILITY MODELS

#### PYTHON COMPATIBLE MODELS

LENGTH	GAS HOSE	POWER CABLE	
		(A/C)	(W/C)
15 ft (4.6 m)	552-0241-15	843-0640-15	005-0388-15
25 ft (7.6 m)	552-0241-25	843-0640-25	005-0388-25
35 ft (10.7 m)	552-0241-35	843-0640-35	005-0388-35
50 ft (15.2 m)	552-0241-50	843-0640-50	005-0388-50

#### PYTHON COMPATIBLE MODELS - CONTROL CABLES

LENGTH	(LINCOLN, 7 PIN) (EURO, 7 PIN) (MILLER, 14 PIN) (FRONIUS, 9 PIN)			
	15 ft (4.6 m)	005-0690	005-0380-15	005-0381-15
25 ft (7.6 m)	005-0691	005-0380-25	005-0381-25	005-0381-25
35 ft (10.7 m)	005-0740	005-0380-35	005-0381-35	005-0381-35
50 ft (15.2 m)	005-0692	005-0380-50	005-0381-50	005-0381-50

#### PYTHON COMPATIBILITY WATER HOSE - BLUE

LENGTH	(LINCOLN, 7 PIN) (EURO, 7 PIN) (MILLER, 14 PIN) (FRONIUS, 9 PIN)			
	15 ft (4.6 m)	552-0239-15		
25 ft (7.6 m)	552-0239-25			552-0238-25
35 ft (10.7 m)	552-0239-35			552-0238-35
50 ft (15.2 m)	552-0239-50			552-0238-50

#### PYTHON COMPATIBILITY WATER HOSE - RED

LENGTH	(LINCOLN, 7 PIN) (EURO, 7 PIN) (MILLER, 14 PIN) (FRONIUS, 9 PIN)			
	15 ft (4.6 m)	552-0209*		

\* Used for all lead assembly lengths

#### OPTIONAL LEAD ASSEMBLY COMPONENTS

LENGTH	ULTRA FLEX POWER CABLE*
15 ft (4.6 m)	843-0715-15
25 ft (7.6 m)	843-0715-25
35 ft (10.7 m)	843-0715-35
50 ft (15.2 m)	843-0715-50

#### ALUMINUM WELDING ONLY (COMPATIBLE GUNS)

LENGTH	CONDUIT ASSEMBLY
15 ft (4.6 m)	615-0620-15
25 ft (7.6 m)	615-0620-25
35 ft (10.7 m)	615-0620-35
50 ft (15.2 m)	615-0620-50

#### HARD WIRE WELDING\* ONLY

LENGTH	FLAT SPIRAL STEEL CONDUIT ASSEMBLY
15 ft (4.6 m)	615-0621-15
25 ft (7.6 m)	615-0621-25
35 ft (10.7 m)	615-0621-35
50 ft (15.2 m)	615-0621-50

\*Air Cooled models only

\*Steel, stainless steel and flux core steel wires  
See accessories and consumables for liners and contact tips (pgs 21-24)