

Python® LX Compatibility

All Cobramatic® and Cobramatic compatible guns are available in lengths of 15 ft, 25 ft, 35 ft, and 50 ft.

Lincoln Compatible guns used with Lincoln Power Feed 25M (model K2536-4) require a kit for adaptability. Call factory for details.



LINCOLN, 7 PIN COMPATIBILITY

AIR COOLED	
LENGTH	MODEL NUMBER
15 ft (4.6 m)	270-815
25 ft (7.6 m)	270-825
35 ft (10.7 m)	270-835
50 ft (15.2 m)	270-850
WATER COOLED	
15 ft (4.6 m)	271-815
25 ft (7.6 m)	271-825
35 ft (10.7 m)	271-835
50 ft (15.2 m)	271-850

MILLER, 14 PIN COMPATIBILITY

AIR COOLED	
LENGTH	MODEL NUMBER
15 ft (4.6 m)	272-815
25 ft (7.6 m)	272-825
35 ft (10.7 m)	272-835
50 ft (15.2 m)	272-850
WATER COOLED	
15 ft (4.6 m)	273-815
25 ft (7.6 m)	273-825
35 ft (10.7 m)	273-835
50 ft (15.2 m)	273-850

FRONIUS, 9 PIN COMPATIBILITY

AIR COOLED	
LENGTH	MODEL NUMBER
15 ft (4.6 m)	274-815
25 ft (7.6 m)	274-825
35 ft (10.7 m)	274-835
50 ft (15.2 m)	274-850
WATER COOLED	
15 ft (4.6 m)	275-815
25 ft (7.6 m)	275-825
35 ft (10.7 m)	275-835
50 ft (15.2 m)	275-850

EURO, 7 PIN COMPATIBILITY

AIR COOLED	
LENGTH	MODEL NUMBER
15 ft (4.6 m)	294-815
25 ft (7.6 m)	294-825
35 ft (10.7 m)	294-835
50 ft (15.2 m)	294-850
WATER COOLED	
15 ft (4.6 m)	295-815
25 ft (7.6 m)	295-825
35 ft (10.7 m)	295-835
50 ft (15.2 m)	295-850

MK Products compatible guns have interchangeable fittings, so you can match as needed for your cooler. Both fittings require a hose retainer. Call factory for pricing.



431-1898
5/16" Hose Retainer



431-1910
Quick Connect Fitting



431-1893* Nipple
753-3379* Left-Hand Threaded Fitting
**Must be ordered together*

GUN LEAD ASSEMBLY COMPONENTS - LX AND MX COMPATIBILITY MODELS

LX AND MX COMPATIBLE MODELS

LENGTH	GAS HOSE	POWER CABLE	
		(A/C)	(W/C)
15 ft (4.6 m)	552-0241-15	843-0640-15	005-0388-15
25 ft (7.6 m)	552-0241-25	843-0640-25	005-0388-25
35 ft (10.7 m)	552-0241-35	843-0640-35	005-0388-35
50 ft (15.2 m)	552-0241-50	843-0640-50	005-0388-50

LX AND MX COMPATIBLE MODELS - CONTROL CABLES

LENGTH	(LINCOLN, 7 PIN) (EURO, 7 PIN) (MILLER, 14 PIN) (FRONIUS, 9 PIN)			
	15 ft (4.6 m)	005-0690	005-0380-15	005-0381-15
25 ft (7.6 m)	005-0691	005-0380-25	005-0381-25	005-0381-25
35 ft (10.7 m)	005-0740	005-0380-35	005-0381-35	005-0381-35
50 ft (15.2 m)	005-0692	005-0380-50	005-0381-50	005-0381-50

LX AND MX COMPATIBILITY WATER HOSE - BLUE

LENGTH	(LINCOLN, 7 PIN) (EURO, 7 PIN) (MILLER, 14 PIN) (FRONIUS, 9 PIN)			
	15 ft (4.6 m)	552-0239-15		
25 ft (7.6 m)	552-0239-25			552-0238-25
35 ft (10.7 m)	552-0239-35			552-0238-35
50 ft (15.2 m)	552-0239-50			552-0238-50

LX AND MX COMPATIBILITY WATER HOSE - RED

(LINCOLN, 7 PIN) (EURO, 7 PIN) (MILLER, 14 PIN) (FRONIUS, 9 PIN)			
552-0209*			552-0211*

* Used for all lead assembly lengths

OPTIONAL LEAD ASSEMBLY COMPONENTS

LENGTH	ULTRA FLEX POWER CABLE*
15 ft (4.6 m)	843-0715-15
25 ft (7.6 m)	843-0715-25
35 ft (10.7 m)	843-0715-35
50 ft (15.2 m)	843-0715-50

ALUMINUM WELDING ONLY (COMPATIBLE GUNS)

LENGTH	CONDUIT ASSEMBLY
15 ft (4.6 m)	615-0620-15
25 ft (7.6 m)	615-0620-25
35 ft (10.7 m)	615-0620-35
50 ft (15.2 m)	615-0620-50

HARD WIRE WELDING* ONLY

LENGTH	FLAT SPIRAL STEEL CONDUIT ASSEMBLY
15 ft (4.6 m)	615-0621-15
25 ft (7.6 m)	615-0621-25
35 ft (10.7 m)	615-0621-35
50 ft (15.2 m)	615-0621-50

*Air Cooled models only

*Steel, stainless steel and flux core steel wires

See accessories and consumables for liners and contact tips (pgs 21-24)